



TeleDis



TSH 2077
AV - COFDM



TSH AV-Out
Best.Nr. / Ord.Nr. 35711

zur Programmierung notwendig
necessary for programming



TSH 2078 PSU
AV - QAM
Standalone



TSH PR
Fernbedien./ remote control
Best.Nr. / Ord.No. 35710



TSH AV IN
AV-Kabel / AV cable
Best Nr. / Ord. Nr. 35714

AV - COFDM

AV - QAM

Typ / Type	TSH 2077	TSH 2078
Artikelnummer / order number	35609	35610
Typ / Type	TSH 2077 PSU	TSH 2078 PSU
Artikelnummer / order number	35877	35878
Eingang / input	2 x AV-Signal/CVBS	2 x AV-Signal/CVBS
Anschluss Eingang /connector IN	2 x 15 Sub-D	2 x 15 Sub-D
Eingang Video / input video	PAL / NTSC / SECAM	PAL / NTSC / SECAM
Eingang Audio / input audio	Mono / Stereo	Mono / Stereo
Modulator		
Modulation / modulation	COFDM	QAM
Ausgangsmodus / output mode	QPSK, QAM 16, 64, / 2k, 8k	QAM 16, 32, 64, 128, 254
Spectralumkehr / spectrum inversion	Normal, Inverted	Normal, Inverted
Ausgangskanal / output channel	E 02 - C 69	E 02 - C 69
Ausgangspegel / output level	typ. 93 dBµV	typ. 93 dBµV
Symbolrate / symbol rate	4-30 Mbps (SCPC/MCPC)	4-30 Mbps (SCPC/MCPC)
MER	33 dB	33 dB
Impedance / impedance	75	75
Betriebstemperatur / working temperature	-10 ... +50 °C	-10 ... +50 °C
Gewicht / weight	1,5 kg	1,5 kg
Maße / dimension (HxTxB / HxDxW)	231 x 148 x 35 mm	231 x 148 x 35 mm